

## Perf-O Grip Stair Treads & Walkway Grating Load Tables

PERF-O GRIP & TRACTION TREAD CARRIER PLATE SPECIFICATIONS			
TREAD WIDTH A	DEPTH B	DIMENSION C	DIMENSION D
5" *	1-1/2" 2"	3/4" 1"	2"
7"	1-1/2" 2"	3/4" 1"	4"
10"	1-1/2" 2"	3/4" 1"	7"
12"	1-1/2" 2"	3/4" 1"	9"

\* PERF-O GRIP STAIR TREAD ONLY.

PERF-O GRIP RECOMMENDED SIZES & SPANS				
SPAN IN.	MATERIAL/ GAUGE	CHANNEL DEPTH IN.	CATALOG NUMBER	WIDTH
UP TO 30"	STEEL 13 GA.	1-1/2	T-P21513 T-P31513 T-P51513 T-P61513	5" 7" 10" 12"
31 TO 48*	STEEL 11 GA.	2	T-P22011 T-P32011 T-P52011 T-P62011	5" 7" 10" 12"
UP TO 42*	ALUM .125	2	T-P220.125-A T-P320.125-A T-P520.125-A T-P620.125-A	5" 7" 10" 12"

PERF-O GRIP WALKWAY LOAD TABLE - 24" & 30" WIDTHS																		
PLANK MATERIAL	WEIGHT LB./FT.	DEPTH INCHES	CATALOG NUMBER	SPAN														
				2'-0"	2'-6"	3'-0"	3'-6"	4'-0"	4'-6"	5'-0"	6'-0"	7'-0"	8'-0"	9'-0"	10'-0"	11'-0"	12'-0"	
STEEL 11 GA. 24" WIDE	11.8	5	P135011W	U	5751	3681	2556	1878	1438	1136	920	639	469	359	284	230	190	160
				D	.02	.02	.04	.05	.06	.08	.10	.14	.19	.25	.31	.39	.47	.56
				C	9504	7604	6336	5431	4752	4224	3802	3168	2715	2376	2112	1901	1728	1584
				D	.01	.01	.02	.03	.04	.05	.06	.08	.11	.15	.19	.23	.28	.34
STEEL 11 GA. 30" WIDE	13.6	5	P165011W	U	3868	2475	1719	1263	967	764	619	430	316	242	191	155	128	107
				D	.01	.02	.03	.04	.05	.06	.08	.12	.16	.20	.26	.32	.39	.46
				C	9534	7627	6356	5448	4767	4237	3813	3178	2724	2383	2119	1907	1733	1539
				D	.01	.01	.02	.03	.04	.05	.06	.08	.11	.15	.19	.23	.28	.33

